



2002 HUMMER H1



4-DOOR WAGON



4-DOOR OPEN TOP

True, the H1 is not for everyone. But then again, many of its capabilities aren't for everyone either. Like climbing a 22 inch vertical wall, navigating a 60% grade, traversing a 40% side slope, or fording 30 inches of water. They're the types of capabilities strictly for those wishing to go places that almost no other vehicle can take them. And we don't just mean geographically.

COMPONENTS & FEATURES

- Engine: V8, 6.5L Turbocharged diesel, electronically controlled
Horsepower: 195 @ 3400 rpm
Torque: 430 lb-ft @ 1800 rpm
• Transmission: 4L80-E 4-speed automatic
• Powertrain: Full-time 4WD with TorqTrac® 4 (TT4) traction system
• Transfer case: New Venture Gear model 242
• Geared hubs: Gear ratio of 1.92:1
• Differential: Zexel Torsen® III torque biasing differential
• Fuel capacity: 25 gallon tank plus 17 gallon auxiliary tank
• Steering: Power assisted
• Brakes: Hydroboost 4-wheel in-board mounted Meritor-WABCO ABS power disc brakes
• Suspension: Independent double A frame with open-end coil springs and hydraulic shock absorbers
• Frame: Steel box section with five cross members

INTERIOR FEATURES

- Cloud Gray cloth interior
• Remote keyless entry
• Power windows (express down for driver)
• Monsoon® audio system with 6-disc CD player/changer and cassette
• Air conditioning with auxiliary rear unit
• Air inflation line with quick connects
• E-Z Kool® glass (windshield, passenger, driver windows)
• Heated windshield
• CTIS controls and in-dash tire pressure gauges

EXTERIOR FEATURES

- 6061 T6 hardened aircraft aluminum body
• Composite hood
• Heavy duty steel bumper towing shackles
• 3/16 in. rocker panel protection constructed from T6 aluminum
• Brush guard
• Driveline protection
• Trailer towing unit with wiring harness
• Heated power mirrors

WHEELS & TIRES

- 17 in. 1-piece cast aluminum wheels
• 37 x 12.5R-17 load range "E" Goodyear Wrangler GSA radial
• Central Tire Inflation System (CTIS) with on-board air compressor
• Tire bead retaining system
• Runflat tire system (NOTE 1)
• Concealed air delivery system

SPECIFICATIONS & PERFORMANCE DATA

- Length: 184.5 in. (NOTE 2)
• Width: 86.5 in. (excluding mirrors)
• Track width: 71.6 in.
• Height:
4-Door Open Top: 77 in.
4-Door Wagon: 75 in.
• Wheelbase: 130 in.
• Ground clearance: 16 in.
• Maximum towed load: (NOTE 3)
4-Door Open Top: 7,986 lb.
4-Door Wagon: 7,646 lb.
• Approach angle (without winch): 72°
• Approach angle (with winch): 47°
• Departure angle: 37.5°
• Runflat capability: 20 miles @ 30 mph (NOTE 1)
• Turning radius: 26.5 ft.

OPTIONAL EQUIPMENT

- 17 in. 2-piece forged aluminum wheels with dual beadlocks and Runflats featuring a fully concealed air delivery system to support CTIS
• 37 x 12.5R-17 load range "E" Goodyear Wrangler MT/R tire with DuraWall puncture resistance technology
• 12,000 lb. winch

HUMMER® like nothing else.™



Black



Bright White



Competition Yellow



Ocean Blue Metallic



Firehouse Red



Metallic Pewter



Silver Metallic



Woodland Green

For more information check out www.HUMMER.com or call us at 1.800.REAL.4WD.

© General Motors Corporation, 2002. All rights reserved. HUMMER and the vehicle's grille are registered trademarks of General Motors Corporation. TorqTrac (TT4/ABS) is a registered trademark of AM General Corporation. GM reserves the right to make changes, at any time and without notice, in prices, colors, materials, equipment, specifications, models and availability. Details and specs may vary according to local regulations and conditions. NOTE 1: For emergency use only, a "get home" capability that will cause tire damage. NOTE 2: The data on this page applies to models without winch and optional accessories. Models with winch are impacted as follows: PAYLOAD: Decrease by 137 lbs.; CURB WEIGHT: Increase by 137 lbs.; LENGTH: Increase by 6 in. NOTE 3: Maximum towing capacity will vary based on vehicle loading. Gross Combination Weight (GCW) of vehicle and trailer cannot exceed 15,300 lbs. for highway use only. A weight-carrying hitch gives your vehicle the capability to tow a maximum weight of 7,500 lbs. A weight-distributing hitch with spring bars may give your vehicle the capability to tow a maximum weight of up to 7,855 lbs., depending on model and payload. These are not necessarily weights the vehicle will tow at sustained highway speeds or varying altitudes. NOTE: The maximum allowable weight your vehicle can tow off-road, no matter what type of hitch is being used, is 5,000 lbs. Consult your local HUMMER dealer for availability of accessories and current specifications. All specifications are based on latest information available at time of printing.